



VT7S12E Dual Channel Vibration Transmitter

Compact. Advanced. Affordable

VT7S12E is the most advanced & Compact Vibration Transmitter. It accepts input directly from ICP type Accelerometer, processes the signal and gives analog output in the form of standard current or voltage; the vibration measurement range is field configurable for acceleration, velocity or displacement. The output signal is usually interfaced with PLC or DCS for monitoring and protection.

VT7S12E Transmitter has two Relay outputs per channel for Alarm, Trip. Also has additional outputs like Buffered output on BNC connector for analysis purpose, and optional RS485 serial port for direct interface with PLC, DCS or SCADA

VT7S12E is aimed for balance of plant equipments like Pumps, Motors, Fans, Blowers, etc to provide monitoring and protection, the unit Employs True-RMS and calculated RMS-Peak measurement techniques, considered best for general machine condition monitoring.

The unit can be field configured and operated by means of front keyboard and display, Relay set points and logic can be set for all application types including fail-safe operation, all configured data is stored in a non-volatile memory.

Features

- Compact DIN Rail mounting
- 4 Digit LED display for Parameter Value & 1 Digit LED display for channel no
- Dual channel (optional single channel)
- Micro Controller based
- Same model Field Configurable for Acceleration, Velocity or Displacement range
- Field configurable by front keys and display
- Transmitter/Input signal health check
- Relay for Alarms/Trip
- Serial Modbus Interface (optional)

Applications

- Balance of Plant Vibration measurement and protection
- Cooling Towers
- Pumps
- Motors
- Gear Boxes
- Blowers
- ID/ FD/ PA Fans
- Air Compressors
- Conveyors

TECHNICAL SPECIFICATIONS

| | | | |
|---------------------------------|---|---|--|
| Input | | Relay Output | |
| No of Channels | Two/One (Optional) | No of Relays | 4 nos (2 nos per channel) |
| Input Type | | Purpose | Alarm/Trip |
| Accelermoter Input | | Rating | 2A@250VAC/30VDC & 5A@250VAC (optional) |
| Type | Remote ICP piezoelectric Accelerometer | Type | C, NO, NC |
| Sensitivity | 100mV/g (Standard) 500mV/g (On Request) | Delay for relay | 05-50 sec to avoid false tripping |
| Dynamic Range | 80 g pk | Communication (Isolated) - Optional | |
| Measurement Parameters | | No of Port | 1 no RS485 |
| Parameter | Range (Field Selectable) | Protocol | Modbus - RTU |
| Acceleration | 0 to 50.0g (RMS, Pk) | Baud Rate | 9600, 19200 |
| Velocity | 0 to 100.0mm/sec (RMS, Pk) | Buffered Output (Available for Vibration input type only) | |
| Displacement | 0 to 2000microns (Pk-Pk) [#] | No of Output | 2 nos |
| | | Output Impedance | <100 ohms |
| | | Frequency Range | 0.5Hz to 10KHz |
| | | Accuracy | 0.25% of Full Range |
| Sensor Excitation current | 4 mA Approx | Power Supply | |
| Scan Time | 150 mSec/Channel | Voltage | 85 to 265VAC, 50/60Hz 18 to 36VDC (optional) |
| Frequency Range (factory set) | High Pass: 2.5Hz, 5 Hz, 10 Hz Low Pass: 1 KHz, 2.5KHz, 10KHz | Consumption | 12 VA max 85 to 265 VAC 7 VA max 18 to 36 VDC |
| Accuracy | ±2% of full span (Input to Display) | Isolation (Withstanding voltage) | |
| Display & Keys | | <ul style="list-style-type: none"> Between primary terminals* and secondary terminals**: At least 1500 V AC for 1 minute Between primary terminals*: At least 1500 V AC for 1 minute Between secondary terminals**: At least 500 V AC for 1 minute | |
| Channel number | 1-Digit, 0.3", Green seven segment LED | * Primary terminals indicate power terminals and Aux Supply terminals. | |
| Measuring Parameter Value | 4-Digit, 0.3", Red seven segment LED | ** Secondary terminals indicate Communication O/P and Power O/P. | |
| Status LEDs | Discrete/Individual RED LEDs, 2 LEDs for Communication, 4 LEDs for Relay, 1 LED for Auto-manual and 2 for input type of channel | Insulation resistance: 20MΩ or more at 500 V DC between power terminals and grounding terminal | |
| Operational Keys | 4 Keys (ENT, UP, DOWN & ESC) | Physical | |
| Output | | Mounting | 35mm DIN rail |
| Analog Output (Isolated) | | Dimension (in mm) | 75 (H) x 70(W) x 110 (D) |
| No of Outputs | One per channel | Weight | 350g |
| Output Types | 4-20mA (standard range) Optional: 0-20mA, 1-5VDC, 0-5VDC, 0-10VDC (Factory set, any one at a time) | Wiring | Terminals for 2.5mm ² wire size |
| Load | 500Ω Max (For current o/p) 3000Ω Min (For voltage o/p) | Enclosure material | ABS Plastic |
| Accuracy | ±0.25% of Full Scale (Display to Output) | Protection | IP20 (except terminals) |
| | | Environmental | |
| | | Operating Temperature | 0 to 55 °C |
| | | Operating Humidity | 30 to 95% RH (non-condensing) |
| | | Storage Temperature | 0 to 85°C |
| | | Warm up time | 15 minutes |

Ordering code

| Model | Channel-1 | Channel-2 | Power Supply | Output Type | Communication o/p |
|---------|-----------|-----------|--------------|-------------|-------------------|
| VT7S12E | X | X | X | X | X |
| | 1 | N | A | N | N |
| | | 1 | B | C | 1 |
| | | | | D | |
| | | | | E | |
| | | | | F | |
| | | | | G | |

Optional at extra cost

| | |
|-------------------|--------------------|
| Compatible Sensor | |
| Sensor Mounting: | Stud/ Pad mounting |
| Sensor Type: | ICP |
| Sensor Output: | 100mV/g |